

DESCRIPTION

SEM Solve is a virgin solvent blend to clean panels prior to refinish or repair.

FEATURES

- Effectively removes adhesive residue, wax, grease, road tar, oil, silicone, paint overspray and bug remnants
- Easy to use
- Leaves no residue

SUITABLE SUBSTRATES

- Bare Metal
- Primed or Painted Surfaces
- SMC & Plastic – Limit Exposure

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
38371	SEM Solve	Clear	Gallon
38373	SEM Solve	Clear	Aerosol
38374	SEM Solve	Clear	Quart
38375	SEM Solve	Clear	5 Gallon
VOC Actual (38371, 38374, 38375):		773 g/L	
VOC Actual (38373):		712 g/L	

Check local VOC regulations to ensure compliance in your area.

HANDLING AND APPLICATION

MIXING:

Ready to use.

APPLICATION:

Apply **SEM Solve** directly to surface or clean cloth. Wipe surface with enough material to adequately float contaminants out of sand scratches. Wipe dry in one direction with a clean, lint-free cloth, turning and changing cloths often. If **SEM Solve** air dries on the surface, re-wet and dry completely with a clean, lint free cloth. Do not leave solvent cloth on painted surface.

Note:

Avoid prolonged contact with SMC, fiberglass and plastic. Do not saturate exposed fibers of SMC and fiberglass.



Check local VOC regulations to ensure compliance of all products in your area.

STORAGE:

SEM Solve should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **38373** is 5 years when stored under normal conditions, while the shelf life for **38371**, **38374** and **38375** is unlimited.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.